

Specifications


备注 (Remark)

1. 材料 (MATERIAL)

胶芯: PA6T+30%G. F UL94V-0, 颜色: 黑色.
 Housing: PA6T+30%G. F UL94V-0, Color: Black
 四方针: 黄铜, 镍底30u"MIN, 表面镀金0.8u"MIN
 Contact: Brass, 0.8u"MIN GOLD PLATING OVER ALL
 30u" MIN NICKEL UNDERPLATING OVER ALL

2. 特性 (characteristics):




额定电流: 3 AMP
 Raring Current: 3 AMP.
 接触阻抗: 20 mΩ MAX.
 Contact Resistance: 20 mΩ MAX.
 绝缘阻抗: 1000 MΩ MIN.
 Insulating Resistance: 1000 MΩ MIN.
 耐电压: AC 500V.
 Withstanding Voltage: AC 500V.
 温度范围: -40°C to+105°C
 Temperture Range: -40°C to+105°C



Ordering Information

P125-11 XX XX X R XXX X 1

HEIGHT OF HOUSING	NO.OF PINS PER ROW	Contact Plating		INSULATOR MATERIAL:	LENGTH OF TERMINAL	PACKING
25:2.50mm	1~40P	Full Of Gold	Semi-gold	B:PA6T		A:PE Bag
		A0=0.8u"	B0=0.8U"	C:PA9T		B:Tape & Reel
		A1=1u"	B1=1U"	D:LCP		C:Tube
		A2=1.5u"	B2=1.5U"			D:Tube+CAP
		A3=2u"	B3=2U"			E:Tray
		A4=3u"	B4=3U"			
		A5=5u"	B5=5U"			
		A6=10u"	B6=10U"			
		A7=15u"	B7=15U"			
		A8=20u"	B8=20U"			
		A9=30u"	B9=30U"			
		S1=Ordinary Tin Plated				
		S2=Matte Tin Plated				
		S3=Tin-plated High-temperature				



OPERATION		SCALE		Fit		东莞市宇熙精密连接器有限公司 Dongguan Yuxi Electronic Co.,Ltd.	
X.X	±0.25	UNIT		MM			
X.XX	±0.20	SIZE	A4	DESIGN	卢小强	PART NO.	P125-11XXXXRXXX1
X.XXX	±0.10	SHEET	1/1	CHECK		TITLE:	2.54mm 单排弯针 塑高2.5 桥型
Angle	±3°	PROJ.		APPROVE		Customer No.	
DIM	TOL						

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE
-----	------	--------------------------	--------	---------