



Ordering Information

IDC4 - XX 3 52 XX A Y X 2

NO. OF PINS 10-100P	Contact Plating		INSULATOR MATERIAL: A: PBT	B: Black G: Grey427 E: Grey413 W: White U: Blue
	Full Of Gold	Semi-gold		
	A0=0.8u"	B0=0.8u"		
	A1=1u"	B1=1u"		
	A2=1.5u"	B2=1.5u"		
	A3=2u"	B3=2u"		
	A4=3u"	B4=3u"		
	A5=5u"	B5=5u"		
	A6=10u"	B6=10u"		
	A7=15u"	B7=15u"		
A8=20u"	B8=20u"			
A9=30u"	B9=30u"			
S1=Ordinary Tin Plated S2=Matte Tin Plated S3=Tin-plated High-temperature				

Specifications

备注 (Remark)

1. 材料 (MATERIAL)
 胶芯: PBT+30%G. F UL94V-0, 颜色: 黑色.
 Housing: PBT+30%G. F UL94V-0, Color: Black
 端子: 磷/青铜, 镀底30u"MIN, 表面镀金1u"MIN
 Contact: Phosphor bronze, 1u"MIN GOLD PLATING OVER ALL
 30u" MIN NICKEL UNDERPLATING OVER ALL

2. 特性 (characteristics):
 额定电流: 1 AMP
 Raring Current: 1 AMP.
 接触阻抗: 20 mΩ MAX.
 Contact Resistance: 20 mΩ MAX.
 绝缘阻抗: 1000 MΩ MIN.
 Insulating Resistance: 1000 MΩ MIN.
 耐电压: AC 500V.
 Withstanding Voltage: AC 500V.
 温度范围: -40°C to +105°C
 Temperature Range: -40°C to +105°C

				OPERATION		SCALE		Fit		东莞市宇熙精密连接器有限公司 Dongguan Yuxi Electronic Co., Ltd.	
				X.X	±0.25	UNIT		MM			
				X.XX	±0.20	SIZE	A4	DESIGN	卢小强	PART NO.	IDC4-XX252XXAYX2
				X.XXX	±0.10	SHEET	1/1	CHECK		TITLE:	1.27*2.54 IDC 塑高5.2 Y型 三件式 带凸点
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	Angle	±3°	PROJ.	APPROVE		Customer No.	