



Ordering Information

DIP1- XX 2 42 XX A Y X 1

NO.OF PINS
6-64P

Contact Plating
Full Of Gold

INSULATOR
MATERIAL:

B:Black
G:Grey427

A0=0.8u"

Semi-gold
B0=0.8u"

A:PBT

E:Grey413

A1=1u"

B1=1U"

B:PA6T

W:White

A2=1.5u"

B2=1.5U"

C:PA9T

U:Blue

A3=2u"

B3=2U"

D:LCP

A4=3u"

B4=3U"

A5=5u"

B5=5U"

A6=10u"

B6=10U"

A7=15u"

B7=15U"

A8=20u"

B8=20U"

A9=30u"

B9=30U"

S1=Ordinary Tin Plated

S2=Matte Tin Plated

S3=Tin-plated High-temperature

Specifications

备注 (Remark)

1. 材料 (MATERIAL)

胶芯: PBT+30%G. F UL94V-0, 颜色: 黑色.

Housing: PBT+30%G. F UL94V-0, Color: Black

端子: 磷/青铜, 镀底30u"MIN, 表面镀金1u"MIN

Contact: Phosphor bronze, 1u"MIN GOLD PLATING OVER ALL
30u" MIN NICKEL UNDERPLATING OVER ALL

2. 特性 (characteristics):

额定电流: 3 AMP

Rating Current: 3 AMP.

接触阻抗: 20 mΩ MAX.

Contact Resistance: 20 mΩ MAX.

绝缘阻抗: 1000 MΩ MIN.

Insulating Resistance: 1000 MΩ MIN.

耐电压: AC 500V.

Withstanding Voltage: AC 500V.

温度范围: -40°C to +105°C

Temperature Range: -40°C to +105°C

				OPERATION		SCALE		Fit		东莞市宇熙精密连接器有限公司 Dongguan Yuxi Electronic Co., Ltd.	
				X.X	±0.25	UNIT		MM			
				X.XX	±0.20	SIZE	A4	DESIGN	卢小强	PART NO.	DIP1-XX242XXAYX1
				X.XXX	±0.10	SHEET	1/1	CHECK		TITLE:	2.54mm DIP 塑高4.2
REV	DATE	MODIFICATION	DESCRIPTION	CHANGE	APPROVE	Angle	±3°	APPROVE		Customer No.	
						DIM	TOL	PROJ.			