

Specifications

備注 (Remark)

1. 材料 (Material)

膠芯: PA9T/LCP+30%G. F UL94V-0, 顏色: 黑色

Housing: PA9T/LCP+30%G. F UL94V-0, Color: Black

端子: 黃銅

Contact: Brass

2. 特性 (characteristics):

額定電流: 2.0AMP

Rating Current: 2.0AMP

接觸阻抗: 20mΩ Max

Contact Resistance: 20mΩ Max

絕緣阻抗: 1000MΩ Min


Insulating Resistance: 1000 MΩ Min

耐電壓: AC 500V/分鐘


Withstanding Voltage: AC 500V/Minute

溫度範圍: -40° C to +105° C

Temperture Range: -40° C to +105° C












P2XX-14XXXXXSXXXX1
L=A+B+H



P2XX-14XXXXXRXXXX1
L=A+B+D+H+1.0

Mating With/配對母座:
F263/293



Dimension antitheses list			
ITEM	A	B	H
Standard	2.80	4.0/6.0	1.5
Alternate			2.0

Dimension antitheses list				
ITEM	A	B	D	H
Standard	2.80	4.0/6.0	0.75	1.5
Alternate				2.0

PIN HEADER

P 2 1 5 - 1 4

P 2 2 0 - 1 4

X X

X X

X

X

X X X

X

1

No. Of Pins
Per Row
02~40P

Contact Plating
Full Of Gold A0=0.8u"
Semi-Gold B0=0.8u"

A9=30u" B9=30u"
S1=Ordinary Tin Plated
S2=Matte Tin Plated
S3=Tin-plated High-temperature

Insulator Material:
A:PBT
B:PA6T
C:PA9T
D:LCP

Contact Shape:
S: Straight
R: Right Angle

Length Of
Terminal

Packing
A: PE Bag
B: Tape & Reel
C: Tube
D: Tube+CAP
E: Tray

Http://www.yxcon.com

E-mail:yx@yxcon.com

YUXI DONGGUAN (東莞)
YUXI TAIWAN (台灣)

TEL:+86 769 85397456
TEL:+886 3313 2933

FAX:+86 769 85396015
FAX:+886 3313 2935