

Specifications

備注 (Remark)

1. 材料 (Material)

膠芯:PA9T/LCP+30% G. F UL94V-0, 顏色: 黑色

Housing:PA9T/LCP+30% G. F UL94V-0, Color:Black

端子:磷銅

Contact:Phosphor Bronze

2. 特性 (characteristics):

額定電流:2.0AMP

Rating Current:2.0AMP

接觸阻抗:20mΩ Max

Contact Resistance:20mΩ Max

絕緣阻抗:1000MΩ Min


Insulating Resistance:1000 MΩ Min

耐電壓: AC 500V/分钟


Withstanding Voltage:AC 500V/Minute

溫度範圍: -55° C to+125° C


Temperture Range: -55° C to+125° C



F263-13XXXXXSYX1






F263-13XXXXXRYX1







F263-23XXXXXSYX1



Mating With/配對公座:
P215/P220





Recommended P.C.B Layout



Recommended P.C.B Layout



Recommended P.C.B Layout



Dimension antitheses list	
ITEM	C
Standard	
Alternate	

F 2 6 3 - 1 3

F 2 6 3 - 2 3

X X

No.Of Pins
Per Row
02~40P

X X

Contact Plating

Full Of Gold A0=0.8u"
Semi-Gold B0=0.8U"

A9=30u" B9=30U"

S1=Ordinary Tin Plated

S2=Matte Tin Plated

S3=Tin-plated High-temperature

X

Insulator Material:

B:PA6T
C:PA9T
D:LCP

X

Contact Shape:

S:Straight
R:Right Angle

Y

Packing

A:PE Bag
B:Tape & Reel
C:Tube
D:Tube+CAP
E:Tray

X

1

Http://www.yxcon.com

E-mail:yx@yxcon.com

YUXI DONGGUAN (東莞)
YUXI TAIWAN (台灣)

TEL:+86 769 85397456
TEL:+886 3313 2933

FAX:+86 769 85396015
FAX:+886 3313 2935