

Specifications

备注 (Remark)

1. 材料 (MATERIAL)

胶芯: PA6T+30%G.F UL94V-0, 颜色: 黑色.

Housing: PA6T+30%G.F UL94V-0, Color: Black

四方针: 黄铜, 镍底30u"MIN, 表面镀金0.8u"MIN

Contact: Brass, 0.8u"MIN GOLD PLATING OVER ALL
30u" MIN NICKEL UNDERPLATING OVER ALL

2. 特性 (characteristics):

额定电流: 1 AMP

Rating Current: 1 AMP.

接触阻抗: 20 mΩ MAX.

Contact Resistance: 20 mΩ MAX.

绝缘阻抗: 1000 MΩ MIN.


Insulating Resistance: 1000 MΩ MIN.

耐电压: AC 500V.

Withstanding Voltage: AC 500V.

温度范围: -40°C to+105°C





Temperature Range: -40°C to+105°C



Ordering Information

P3XX-12 XX XX X S XXX X 1

HEIGHT OF HOUSING	NO.OF PINS PER ROW	Full Of Gold	Semi-gold	INSULATOR MATERIAL: OF	LENGTH OF TERMINAL	PACKING
08: 0.8mm	2-50P	A0=0.8u"	B0=0.8u"	B:PA6T		A:PE Bag
10: 1.0mm		A1=1u"	B1=1u"	C:PA9T		B:Tape & Reel
15: 1.5mm		A2=1.5u"	B2=1.5u"	D:LCP		C:Tube
		A3=2u"	B3=2u"			D:Tube+CAP
		A4=3u"	B4=3u"			E:Tray
		A5=5u"	B5=5u"			
		A6=10u"	B6=10u"			
		A7=15u"	B7=15u"			
		A8=20u"	B8=20u"			
		A9=30u"	B9=30u"			
		S1=Ordinary Tin Plated				
		S2=Matte Tin Plated				
		S3=Tin-plated High-temperature				



ITEM	A	B	H
Standard	1.8	1.8 3.0 4.0	0.8 1.0 1.5
Alternate			

				OPERATION		SCALE		Fit		东莞市宇熙精密连接器有限公司 Dongguan Yuxi Electronic Co.,Ltd.	
				X.X	±0.25	UNIT		MM			
				X.XX	±0.20	SIZE	A4	DESIGN	卢小强	PART NO.	P3XX-12XXXXXXX1
				X.XXX	±0.10	SHEET	1/1	CHECK		TITLE:	1.27mm 排针 双排 180度
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	Angle	±3°	PROJ.	APPROVE		Customer No.	