

# Specifications

备注 (Remark)

1. 材料 (MATERIAL)

胶芯: PA6T+30%G.F UL94V-0, 颜色: 黑色.

Housing: PA6T+30%G.F UL94V-0, Color: Black

端子: 磷铜, 镍底30u"MIN, 表面镀金1u"MIN

Contact: Phosphor, 1u"MIN GOLD PLATING OVER ALL  
30u" MIN NICKEL UNDERPLATING OVER ALL

2. 特性 (characteristics):

额定电流: 1 AMP

Rating Current: 1 AMP.

接触阻抗: 20 mΩ MAX.

Contact Resistance: 20 mΩ MAX.

绝缘阻抗: 1000 MΩ MIN.

Insulating Resistance: 1000 MΩ MIN.

耐电压: AC 500V.

Withstanding Voltage: AC 500V.

温度范围: -40°C to+105°C

Temperture Range: -40°C to+105°C

# Ordering Information

F334-12 XX XX X SU X 1

NO. OF PINS  
PER ROW  
2-50P

Contact Plating

Full Of Gold

A0=0.8u"

A1=1u"

A2=1.5u"

A3=2u"

A4=3u"

A5=5u"

A6=10u"

A7=15u"

A8=20u"

A9=30u"

S1=Ordinary Tin Plated

S2=Matte Tin Plated

S3=Tin-plated High-temperature

INSULATOR

MATERIAL:

B:PA6T

C:PA9T

D:LCP

PACKING






A:PE Bag

B:Tape & Reel

C:Tube

D:Tube+CAP

E:Tray



REV		DATE		MODIFICATION DESCRIPTION		CHANGE		APPROVE		OPERATION		SCALE		Fit		Yxcon 东莞市宇熙精密连接器有限公司	
										X.X	±0.25	UNIT		MM	Dongguan Yuxi Electronic Co.,Ltd.		
										X.XX	±0.20	SIZE	A4	DESIGN	卢小强	PART NO.	F334-12XXXXXSUX1
										X.XXX	±0.10	SHEET	1/1	CHECK		TITLE:	1.27mm 双排母 塑高3.4 180度 U型
										Angle	±3°	PROJ.	☉	APPROVE		Customer No.	
										DIM	TOL						