

	1	2	3	4	5	6	7	8	9	10																														
A					Stright pin connector ultralow profile height3.0mm::solder tail single row Availability from:1 to 40 contacts Standard number of contacts 5, 6, 8, 9, 10, 11, 12, 14, 16, 17, 20, 25, 32 and 40						Ordering Information RP130-X XX X X X S 100 1 <table><tr><td>HEIGHT OF HOUSING</td><td>1:Single-Row</td><td>2:Dual-Row</td><td>30:3.0mm</td><td>NO.OF PINS PER ROW</td><td>1~40P</td><td>2~40P</td><td>0:No Pitch</td><td>1:1.27</td><td>2:2.00</td><td>3:2.54</td><td>4:7.62</td><td>5:10.16</td><td>6:15.24</td><td>7:22.86</td><td>A=1u"</td><td>B=2u"</td><td>C=5u"</td><td>D=10u"</td><td>E=15u"</td><td>F=30u"</td><td>A:PBT</td><td>B:PA6T</td><td>C:PA9T</td><td>D:LCP</td><td>G:PPS</td><td>LENGTH OF TERMINAL</td></tr></table>		HEIGHT OF HOUSING	1:Single-Row	2:Dual-Row	30:3.0mm	NO.OF PINS PER ROW	1~40P	2~40P	0:No Pitch	1:1.27	2:2.00	3:2.54	4:7.62	5:10.16	6:15.24	7:22.86	A=1u"	B=2u"	C=5u"	D=10u"	E=15u"	F=30u"	A:PBT	B:PA6T	C:PA9T	D:LCP	G:PPS	LENGTH OF TERMINAL	A
HEIGHT OF HOUSING	1:Single-Row	2:Dual-Row	30:3.0mm	NO.OF PINS PER ROW	1~40P	2~40P	0:No Pitch	1:1.27	2:2.00	3:2.54	4:7.62	5:10.16	6:15.24	7:22.86	A=1u"	B=2u"	C=5u"	D=10u"	E=15u"	F=30u"	A:PBT	B:PA6T	C:PA9T	D:LCP	G:PPS	LENGTH OF TERMINAL														
B													B																											
C					Stright pin connector ultralow profile height3.0mm:solder tail double row Availability from:2 to 80 contacts Standard number of contacts 20, 56 60 and 72								C																											
D													D																											
E					Stright pin connector height 4.1mm:solder tail, single row Availability from:1 to 40 contacts Standard number of contacts 5, 6, 8, 9, 10, 11, 12, 14, 16, 17, 20, 25, 30, 32and 40								E																											
F													F																											
G					Stright pin connector height 4.1mm:solder tail, double row Availability from:2 to 80 contacts Standard number of contacts 20, 56 60 and 72								G																											
H													H																											
					OPERATION		SCALE		Fit		 东莞市宇熙精密连接器有限公司 Dongguan Yuxi Electronic Co.,Ltd.																													
					X.X	±0.25	UNIT		MM																															
					X.XX	±0.20	SIZE		A4	DESIGN	卢小强	PART NO.																												
					X.XXX	±0.10	SHEET		1/1	CHECK		TITLE:																												
					Angle	±3°	PROJ.		APPROVE		Customer No.																													
					DIM	TOL																																		
REV	DATE	MODIFICATION DESCRIPTION			CHANGE	APPROVE																																		
1					4																																			
2					5																																			
3					6																																			
4					7																																			
5					8																																			
6					9																																			
7					10																																			
8																																								
9																																								
10																																								

Specifications

Insulator : Black glass filled polyester PPS-GF30-FR
Fiammability : UL94V-0
Sleeve : Brass CuZn 36Pb3(36000)
Mating pin Ø : 0.45 mm/0.48mm
Mechancial life : min 500 cycles
Rated current : 3Amp
Contact resistance: Max 10mΩ
Dielectric resistance : Min 1000V_{RMS}

东莞市宇熙精密连接器有限公司
Dongguan Yuxi Electronic Co.,Ltd.

卢小强 PART NO. RP130-XXXXXS1001
TITLE: 2.54圆孔排针 塑高3.0 180度 L=10.0