

**Specifications**

**Wafer**

備注 (Remark)

1. 材料 (Material)



膠芯: PA66 UL94V-0

Housing: PA66 UL94V-0

端子: 黃銅

Contact: Brass



2004WW-XXS-NOSN



Recommended P.C.B Layout



2004WW-XXS-NOSN



Poles	Dimensions (mm)	
	A	B
02	2.00	5.85
03	4.00	7.85
04	6.00	9.85
05	8.00	11.85
06	10.00	13.85
07	12.00	15.85
08	14.00	17.85
09	16.00	19.85
10	18.00	21.85
11	20.00	23.85
12	22.00	25.85
13	24.00	27.85
14	26.00	29.85
15	28.00	31.85

2004WW-XXS-NOSN	Nylon 66 UL 94V-0	Brass	Tin-Plated	2004H	1,000Pcs
PART NO	Material	Material(Pin)	Finish(Pin)	Mates With SWB Housing	Q'ty/Bag

**Wafer**

備注 (Remark)

1. 材料 (Material)



膠芯: PA66 UL94V-0

Housing: PA66 UL94V-0

端子: 黃銅

Contact: Brass



2004WR-XX-NOSN1



Recommended P.C.B Layout



2004WR-XX-NOSN1



Poles	Dimensions (mm)		
	A	B	C
02	2.00	5.96	5.96
03	4.00	7.96	7.96
04	6.00	9.96	9.96
05	8.00	11.96	11.96
06	10.00	13.96	13.96
07	12.00	15.96	15.96
08	14.00	17.96	17.96
09	16.00	19.96	19.96
10	18.00	21.96	21.96
11	20.00	23.96	23.96
12	22.00	25.96	25.96
13	24.00	27.96	27.96
14	26.00	29.96	29.96
15	28.00	31.96	31.96

2004WR-XX-NOSN	Nylon 66 UL 94V-0	Brass	Tin-Plated	2004H	1,000Pcs
2004WR-XX-NOSN1			Sn 120U*Min. Over 30U* Ni		
PART NO	Material	Material(Pin)	Finish(Pin)	Mates With SWB Housing	Q'ty/Bag

W

WAFER