

Specifications

备注 (Remark)

1. 材料 (MATERIAL)

胶芯: PA6T+30%G.F UL94V-0, 颜色: 黑色.

Housing: PA6T+30%G.F UL94V-0, Color: Black

端子: 磷/青铜, 镍底30u"MIN, 表面镀金1u"MIN

Contact: Phosphor bronze, 1u"MIN GOLD PLATING OVER ALL

30u" MIN NICKEL UNDERPLATING OVER ALL

2. 特性 (characteristics):

额定电流: 3 AMP

Rating Current: 3 AMP.

接触阻抗: 20 mΩ MAX.

Contact Resistance: 20 mΩ MAX.

绝缘阻抗: 1000 MΩ MIN.

Insulating Resistance: 1000 MΩ MIN.

耐电压: AC 500V/分钟.

Withstanding Voltage: AC 500V/Minute.

温度范围: -40° C to +105° C

Temperture Range: -40° C to +105° C

Ordering Information

F183-22 XX XX X SY X 1

NO. OF PINS
PER ROW
2-40P

Contact
Full of Gold

Plating
Semi-gold

INSULATOR
MATERIAL:

PACKING
A: PE Bag

A0=0.8u"

B0=0.8u"

A: PBT

B: Tape & Reel

A1=1u"

B1=1u"

B: PA6T

C: Tube

A2=1.5u"

B2=1.5u"

C: PA6T

D: Tube+CAP

A3=2u"

B3=2u"

D: LCP

E: Tray

A4=3u"

B4=3u"

A5=5u"

B5=5u"

A6=10u"

B6=10u"

A7=15u"

B7=15u"

A8=20u"

B8=20u"





A9=30u"

B9=30u"

S1=Ordinary Tin Plated

S2=Matte Tin Plated

S3=Tin-plated High-temperature



				OPERATION		SCALE		Fit		Yxcon 东莞市宇熙精密连接器有限公司	
				X.X	±0.25	UNIT		MM		www.yxcon.com	Dongguan Yuxi Electronic Co., Ltd.
				X.XX	±0.20	SIZE	A4	DESIGN	周芳杰 2021.6.28	PART NO.	F183-22XXXXXXSYX1
				X.XXX	±0.10	SHEET	1/1	CHECK		TITLE	2.54间距 塑高8.3 双排母 双塑 180度 Y型
				Angle	±3°	PROJ.		APPROVE		Customer No.	
REV	DATE	SYMBOL	MODIFICATION DESCRIPTION			DIM	TOL				